

Material Safety Data Sheet

HAZARD RATING	0	0	0
4-EXTREME	3-HIGH	2-MODERATE	1-SLIGHT
0-INSIGNIFICANT	*SEE SECTION 5		
TOXICITY	1	0	SPECIAL
REACTIVITY	0	0	

QUICK IDENTIFIER (In Plant Common Name)

1065 - 1066 - 1067

Manufacturer's Name CROSSFIELD PRODUCTS CORP.

Emergency Telephone No. 908-245-2800

Address 140 VALLEY ROAD
ROSELLE PARK, NJ 07204

Other Information Calls

Signature of Person Responsible for Preparation

Date Prepared 1-23-91

SECTION 1 - IDENTITY

Common Name: (used on label) (Trade Name & Synonyms) DEX-O-TEX G-26 PASTE, TYPE II

Cas No. 50-00-0

Chemical Name STYRENE BUTADIENE LATEX

Chemical Family SAME

Formula N.A. (BLEND)

SECTION 2 - HAZARDOUS INGREDIENTS

Principal Hazardous Component(s) (chemical & common name(s))	%	Threshold Limit Value (units)
STYRENE BUTADIENE POLYMER	9003-55-0	30% WEIGHT MAX. %

SECTION 3 - PHYSICAL & CHEMICAL CHARACTERISTICS (Fire & Explosion Data)

Boiling Point	212°F.	Specific Gravity (H ₂ O=1)	1.01 - 1.02	Vapor Pressure (mm Hg)	AS WATER
Percent Volatile by Weight	70-71%	Vapor Density (Air = 1)	AS WATER	Evaporation Rate (_____ = 1)	AS WATER
Solubility in Water	DISPERSIBLE	Reactivity in Water			
Appearance and Odor	MILKY WHITE LIQUID EMULSION - SLIGHT NH ₃ ODOR				

Flash Point	ABOVE 212°F	Flammable Limits in Air % by Volume	N.A.	Lower	Upper	Extinguisher Media	WATER/CO ₂ /DRY CHEMICAL	Auto-Ignition Temperature	N.A.
-------------	-------------	-------------------------------------	------	-------	-------	--------------------	-------------------------------------	---------------------------	------

Special Fire Fighting Procedures FIRE FIGHTERS SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS TO AVOID INHALATION OF SMOKE OR VAPORS.

Unusual Fire and Explosion Hazards NONE KNOWN.

SECTION 4 - PHYSICAL HAZARDS

QUICK IDENTIFIER (In Plant Common Name) 1065-1066-1067

Stability Unstable
Stable Conditions
to Avoid

NON-REACTIVE, MAY COAGULATE IF FROZEN AT 32°F.

Incompatibility
(Materials to Avoid)

N.A.

Hazardous
Decomposition Products

N.A.

Hazardous Polymerization May Occur
Will Not Occur Conditions
to Avoid

N.A.

SECTION 5 - HEALTH HAZARDS

Threshold
Limit ValueSigns and
Symptoms of Exposure1. Acute
Overexposure

CONTACT WITH SKIN MAY CAUSE IRRITATION OR RASH-EYES-SLIGHT IRRITATION

2. Chronic
Overexposure

NOT KNOWN.

Medical Conditions Generally
Aggravated by Exposure

ANYONE WHO IS PRONE TO SKIN ALLERGIES.

Chemical Listed as Carcinogen
or Potential Carcinogen

NO

National Toxicology
ProgramYes
No I.A.R.C.
MonographsYes
No

OSHA

Yes
No OSHA Permissible
Exposure Limit

3 PPM

ACGIH Threshold
Limit Value

1 PPM

Other Exposure
Limit Used

N.A.

Emergency and
First Aid Procedures

1. Inhalation

MOVE SUBJECT TO FRESH AIR.

2. Eyes

FLUSH WITH WATER FOR 15 MINUTES AND CALL PHYSICIAN.

3. Skin

WASH AFFECTED AREAS WITH SOAP AND WATER - REMOVE CONTAMINATED CLOTHING.

4. Ingestion

INDUCE VOMITING AND CALL PHYSICIAN AT ONCE.

SECTION 6 - SPECIAL PROTECTION INFORMATION

Respiratory Protection
(Specify Type)NONE REQUIRED IF GOOD VENTILATION IS MAINTAINED - IF NOT, USE RESPIRATOR
MSHA/NIOSH APPROVED.

Ventilation

Local
Exhaust

X

Mechanical
(General)

X

Special

Other

Protective
Gloves

CHEMICAL RESISTANT OR RUBBER

Eye
Protection

CHEMICAL GOGGLES

Other Protective
Clothing or Equipment

AS REQUIRED TO PREVENT SKIN CONTACT.

SECTION 7 - SPECIAL PRECAUTIONS AND SPILL/LEAK PROCEDURES

Precautions to be Taken
in Handling and StoragePROTECTIVE GLOVES AND GOGGLES SHOULD BE WORN - AVOID BREATHING SPRAY
MISTS OR HEATED VAPORS. KEEP PRODUCT FROM FREEZING TO AVOID COAGULATION.Other
PrecautionsSteps to be Taken in Case
Material is Released or SpilledCLEAN UP WITH WATER AND ALLOW TO DRY. SODIUM OR CALCIUM CHLORIDE CAN
BE SPRINKLED ON SPILL WHICH WILL COAGULATE THE LATEX, THEN FLUSH WITH WATER.Waste Disposal
MethodsMAY BE INCINERATED OR DISPOSED OF IN SANITARY LANDFILL IN ACCORDANCE WITH
PROCEDURES USED WITH LATEX PRODUCTS AND WITH LOCAL, STATE AND FEDERAL REGULATIONS.